



SINGLE PHASE PROTECTION RELAY TEST SYSTEM

Utility • Oil & Gas • Industrial



MICROTEST 860

MECHATRONIC Series

MICRO TEST 860 has been created specifically for secondary testing of protection relays. With test outputs of up to 200A a.c., 240V a.c. / d.c., various auxiliary voltages & a built-in timer resolution of 1ms, this unit is ideal for testing the functionality & operation times of protection relays.

The portable MICRO TEST 860 has built-in automatic protection against overcurrent or thermal overload. This equipment is designed for use in high voltage substations & industrial environments.

TECHNICAL SPECIFICATION

AC current output (Continuously adjustable)

Range	No-Load Voltage (min)	Full-Load Current	Duty Cycle (ON circuit / OFF circuit)
0 – 10 A	80 V	10 A	3 min / 15 min
0 – 25 A	25 V	25 A	2 minutes / 15 min
0 – 100 A	10 V	100 A	30 sec / 5 min
	10 V	200 A	1 sec / 5 min

The output transformer is equipped with built-in temperature protection. The primary side is protected by miniature circuit breakers.

AC/DC voltage output (Continuously adjustable)

Range	Duty Cycle (ON circuit / OFF circuit)	Full-Load Current (max)
0-240 V AC	15 min / 30 min	2 A
0-300 V DC	15 min / 30 min	2 A

+ Voltage sources are independently protected by re-triggerable fuses

AC/DC voltage output + (Fixed)

Range	Duty Cycle (ON circuit / OFF circuit)	Full-Load Current (max)
240 V AC	15 min / 30 min	0.5 A
30 V DC	15 min / 30 min	0.5 A
110 V AC 110 V DC	30 min / 30 min	0.5 A

Timer

Range	0.000 s – 999.999 s
Accuracy	1 ms
Max. Test Time	999.999 s
Functions	ON + Timer Start OFF ON OFF + Timer Start
* Unit is built with a triggerable START Command	
* Separate wet and dry contacts available for triggering	

Make / Break Contact

Max current	1 A
Max. voltage	240 V AC/DC
* Contact is protected with a 1A miniature circuit breaker	

Supply Voltage

220 – 260 V AC
50/60 Hz

MEASUREMENTS

* Digital display of output parameters on a backlit LCD

Measured quantities

AC Current		AC Voltage	
Range	0-250 A	Range	0-500 V
Accuracy :± 0.5% of metering (True RMS measurement)			



Set of resistors

1 Ohm (5 A max.)	25 Ohm (2 A max.)	500 Ohm (0.3 A max.)
0.5 Ohm (10 A max.)	100 Ohm (0.7 A max.)	

Weight & Dimensions

Weight	21 Kg
Dimensions	13.5" x 10.0" x 8.0"

Others


Operating Temperature	0 to +55°C
Storage Temperature	-40 to +70°C

* Due to continuing development and improvements, specifications are subject to change without prior notice.

Accessories

MICRO TEST 860 is supplied with the following accessories:

- Mains Cable
- Connection cable set
- Operation Manual
- 1 year warranty



ASIA PACIFIC OFFICE

AGM Power Engineering (Co. No. 001400906-K)
No. 30-3-2, Jalan 2/101C, Cheras Business Centre,
56100 Cheras, Wilayah Persekutuan, Kuala Lumpur,
MALAYSIA

Tel: +603 9132 8542 / 9130 9031
Fax: +603 9132 8500

E-mail: agmpower@streamyx.com